

Date of issue: 01/21/2025

*

Reviewed on 01/21/2025

Page 1/11

Identification	
Product identifier	
Trade name: <u>BD530 Part A</u> (Resin	
Details of the supplier of the safety Manufacturer/Supplier: Big Dog Adhesives LLC 435 Harrison Street ELKHART, IN 46516 USA	y data sheet
Information department: Product s Emergency telephone number: During normal opening times: +1 (24 Hours: CHEMTREC 1-800-424	(520) 271-7313
Hazard(s) identification	
Classification of the substance or i	nixture
GHS02 Flame	
Flammable liquids 2	H225 Highly flammable liquid and vapor.
GHS05 Corrosion	
Eye damage 1	H318 Causes serious eye damage.
GHS07	
Skin irritation 2	H315 Causes skin irritation.
Sensitization - skin 1	H317 May cause an allergic skin reaction.
Specific target organ toxicity (singl	e exposure) 3 H335 May cause respiratory irritation.
Label elements GHS label elements The product is Hazard pictograms GHS02 GHS05 GHS07	classified and labeled according to the Globally Harmonized System (GHS)
Signal word Danger	
Hazard-determining components of	of labeling:
methyl methacrylate	(Contd. on pag

US

Safety Data Sheet acc. to OSHA HCS

Date of issue: 01/21/2025

Reviewed on 01/21/2025

Trade name: BD530 Part A (Resin)

	(Contd. of page 1)
Methacrylic Acid	
dodecyl methacrylate	
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye damage.	
May cause an allergic skin reaction.	
May cause respiratory irritation.	
· Precautionary statements	
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
Ground / bond container and receiving equipment.	
Use explosion-proof [electrical/ventilating/lighting] equipment.	
Use non-sparking tools.	
Take action to prevent static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or sho	wer].
If inhaled: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present	and easy to do.
Continue rinsing.	
Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	lS.
Information pertaining to particular dangers for man and environment:	
Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 3	
$\frac{3}{Fire} = 3$	
3 0 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
$\frac{\text{HEALTH}}{\text{Health}} = *3$	
FIRE 3 $Fire = 3$	
REACTIVITY Reactivity = 0	
Other hazards	
Results of PBT and vPvB assessment	
• PBT: Not applicable.	
• vPvB : Not applicable.	
Classification according to (d)(1)(ii) of § 1910.12000	C
The SDS issuer does not object to the classifications provided by importers or manufacture	ers of precursor
products.	(Contd. or man 2)
	(Contd. on page 3)

Date of issue: 01/21/2025

Reviewed on 01/21/2025

Trade name: BD530 Part A (Resin)

· Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

· D	ang	ger	ous	com	po	nents:	

80-62-6 *methyl methacrylate* 142-90-5 dodecyl methacrylate

79-41-4 Methacrylic Acid

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

• Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

• After inhalation:

- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- *After skin contact: Immediately wash with water and soap and rinse thoroughly.*
- After eve contact: Rinse opened eve for several minutes under running water. Then consult a doctor.
- *After swallowing:* If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

(Contd. on page 4)

(Contd. of page 2)

20-40% *

10-30% * 1-5% *

Date of issue: 01/21/2025

Reviewed on 01/21/2025

Trade name: BD530 Part A (Resin)

(Contd.		
· Protective	e Action Criteria for Chemicals	
80-62-6	methyl methacrylate	17 ppm
142-90-5	dodecyl methacrylate	6.9 ppm
79-41-4	Methacrylic Acid	6.7 ppm
98-82-8	Cumene	50 ppm
· PAC-2:		
80-62-6	methyl methacrylate	120 ppm
142-90-5	dodecyl methacrylate	76 ppm
79-41-4	Methacrylic Acid	61 ppm
98-82-8	Cumene	300 ppm
• PAC-3:		
80-62-6	methyl methacrylate	570 ppm
142-90-5	dodecyl methacrylate	460 ppm
79-41-4	Methacrylic Acid	220 ppm
98-82-8	Cumene	730 ppm

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm

(Contd. on page 5)

[·] Control parameters

US

Date of issue: 01/21/2025

Reviewed on 01/21/2025

Trade name: BD530 Part A (Resin)

DEL	(Contd. of page
	Long-term value: 410 mg/m ³ , 100 ppm
ILV	Short-term value: 100 ppm Long-term value: 50 ppm
	DSEN, A4
79-41	1-4 Methacrylic Acid
REL	Long-term value: 70 mg/m³, 20 ppm Skin
TLV	Long-term value: 20 ppm
	tional information: The lists that were valid during the creation were used as basis.
	sure controls
	opriate engineering controls No further data; see section 7.
	onal protective equipment:
	ral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	hands before breaks and at the end of work.
	d contact with the skin.
	l contact with the eyes and skin. thing equipment:
	se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure u
	ratory protective device that is independent of circulating air.
	ection of hands:
110	Protective gloves
	Protective gloves
	glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	to missing tests no recommendation to the glove material can be given for the product/ the preparation/ t
	ical mixture.
	tion of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	rial of gloves
	election of the suitable gloves does not only depend on the material, but also on further marks of quality as s from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance
	love material can not be calculated in advance and has therefore to be checked prior to the application.
	tration time of glove material
	exact break through time has to be found out by the manufacturer of the protective gloves and has to
obser	ved.
Eye p	protection:
	Tightly sealed goggles
Cilina I	

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- Physical state • Color:

*

Fluid According to product specification

(Contd. on page 6)

US

Date of issue: 01/21/2025

Trade name: BD530 Part A (Resin)

Reviewed on 01/21/2025

	(Contd. of page
Odor:	Characteristic
Odor threshold:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	101 °C (213.8 °F)
Flammability:	Highly flammable.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
Flash point:	10 °C (50 °F)
Auto igniting:	430 °C (806 °F)
Decomposition temperature:	Not determined.
pH-value:	Not determined.
Viscosity:	
Kinematic:	Not determined.
Dynamic:	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/water):	Not determined.
Vapor pressure at 20 °C (68 °F):	47 hPa (35.3 mm Hg)
Vapor pressure:	() hi u (55.5 hin 11g)
Density at 20 °C (68 °F):	0.94086 g/cm ³ (7.85148 lbs/gal)
Relative density	Not determined.
Bulk density:	970 kg/m^3
Vapor density	Not determined.
Particle characteristics	Not applicable.
	Noi uppicuote.
Other information	
Appearance:	
Form:	Fluid
Important information on protection of healt	h and
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosiv
	air/vapor mixtures are possible.
Solvent content:	
VOC content:	< 50 g/L (mixed)
Change in condition	
Evaporation rate	Not determined.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US

Date of issue: 01/21/2025

Reviewed on 01/21/2025

Trade name: BD530 Part A (Resin)

(Contd. of page 6)

Informa Acute to		n toxicological effects
LD/LC5	50 valu	es that are relevant for classification:
ATE (A	cute To	oxicity Estimate)
Oral	LD50	33,000 mg/kg (rat)
Dermal	LD50	12,500 mg/kg (rabbit)
80-62-6	methy	el methacrylate
Oral	LD50	7,872 mg/kg (rat)
79-41-4	Metha	acrylic Acid
Oral	LD50	1,332 mg/kg (mouse)
		1,320 mg/kg (rat)
Dermal	LD50	500 mg/kg (rabbit)

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Strong irritant with the danger of severe eye injury.

• Sensitization: Sensitization possible through skin contact.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

• Interactive effects No interactive effects between components are known.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)				
80-62-6	methyl methacrylate	3		
98-82-8	Cumene	2B		
· NTP (National Toxicology Program)				
98-82-8	Cumene	R		
· OSHA-Ca (Occupational Safety & Health Administration)				
None of	the ingredients is listed.			

· Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

· vPvB: Not applicable.

• Other adverse effects

• Additional ecological information:

· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

(Contd. on page 8)

US

Date of issue: 01/21/2025

Reviewed on 01/21/2025

(Contd. of page 7)

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

Trade name: BD530 Part A (Resin)

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, IMDG, IATA	UN1133	
UN proper shipping name		
DOT, IATA	Adhesives	
IMDG	ADHESIVES	
Transport hazard class(es)		
DOT		
PLAMMABLE LIQUD		
3		
Class	3 Flammable liquids	
Label	3	
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, IMDG, IATA	II	
Environmental hazards:	Not applicable.	
Transport in bulk according to Annex II of		
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L	
2		

Date of issue: 01/21/2025

Reviewed on 01/21/2025

Trade name: BD530 Part A (Resin)

	(Contd. of page
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemle	r code): 33
EMS Number:	F-E,S-D
· Stowage Category	В
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara
· Section 355 (extremely hazardous substances):
None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):
80-62-6 methyl methacrylate
98-82-8 Cumene
• TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.
· Hazardous Air Pollutants
80-62-6 methyl methacrylate
98-82-8 Cumene
· Proposition 65
· Chemicals known to cause cancer:
98-82-8 Cumene
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
· Chemicals known to cause developmental toxicity:
None of the ingredients is listed.
· Carcinogenic categories

· EPA (Er	vironmental Protection Agency)				
80-62-6	methyl methacrylate	E, NL			
98-82-8	Cumene	D, CBD			
· TLV (Threshold Limit Value)					

80-62-6 methyl methacrylate

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 10)

A4

US

Date of issue: 01/21/2025

Reviewed on 01/21/2025

Trade name: BD530 Part A (Resin)

(Contd. of page 9) • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS05 GHS07 · Signal word Danger · Hazard-determining components of labeling: methyl methacrylate Methacrvlic Acid dodecyl methacrylate · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause respiratory irritation. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground / bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take action to prevent static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: -

- Date of previous version 01/02/2025
- Date of preparation 01/21/2025

(Contd. on page 11)

Date of issue: 01/21/2025

Reviewed on 01/21/2025

Trade name: BD530 Part A (Resin)

	(Contd. of page 10)
• Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flammable liquids 2: Flammable liquids – Category 2	
Skin irritation 2: Skin corrosion/irritation – Category 2	
Eye damage 1: Serious eye damage/eye irritation – Category 1	
Sensitization - skin 1: Skin sensitisation – Category 1	
Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3	
• * Data compared to the previous version altered.	
	US -