

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Tuenity	ication	
Product	identifier	
	ame: <u>BD54460 Part B (Hardener)</u> eans of identification	
Article	number: BD54460 Part B (Hardener)	
Manufa Big Dog 435 Hai	of the supplier of the safety data sheet cturer/Supplier: · Adhesives LLC rison Street RT, IN 46516	
Emerge During	tion department: Product safety department ncy telephone number: normal opening times: +1 (520) 271-7313 rs: CHEMTREC 1-800-424-9300	
Hazar	d(s) identification	
Classifi	cation of the substance or mixture	
L	GHS05 Corrosion	
Skin cor Eye dan	rosion 1A H314 Causes severe skin burns and eye damage. hage 1 H318 Causes serious eye damage.	
Sensitize	ution - skin 1 H317 May cause an allergic skin reaction.	
	ements bel elements The product is classified and labeled according to the Globally Harmonized Syst pictograms	tem (GHS).
L R		
GHS0:	5 GHS07	
Signal v	vord Danger	
3,3'-Oxy reaction Hazard Causes	determining components of labeling: bis(ethyleneoxy)bis(propylamine) product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 70 statements severe skin burns and eye damage. use an allergic skin reaction.	0)
may cal		contd. on page 2

Page 1/10

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Trade name: BD54460 Part B (Hardener)

(Contd. of page 1)
· Precautionary statements
Do not breathe dusts or mists.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves / eye protection / face protection.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· Information pertaining to particular dangers for man and environment:
· Classification system:
· NFPA ratings (scale 0 - 4)
Fire = 0 Reactivity = 0 HMIS-ratings (scale 0 - 4)
HEALTH 3 Health = 3FIRE 0 Fire = 0
$\begin{array}{c} \text{REACTIVITY} \\ \hline \end{array} & Reactivity = 0 \end{array}$
· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.
· vPvB: Not applicable.
· Classification according to (d)(1)(ii) of § 1910.12000
The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.
Hazards not otherwise classified
There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard
Communications Standard.
3 Composition/information on ingredients
· Chemical characterization: Mixtures
• Description: Mixture of the substances listed below with nonhazardous additions.
Description: Annuale of the Substances listed before man nonnutariabus autimons.

· Dangerous components:		
4246-51-9 3	2,3'-Oxybis(ethyleneoxy)bis(propylamine)	30-60% *
	eaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average nolecular weight ≤ 700)	15-40% *
	(Co	ntd. on page 3)

– ÚS

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Trade name: BD54460 Part B (Hardener)

(Contd. of page 2)

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- *Suitable extinguishing agents:* Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

	ecautions, protective equipment and emergency procedures ratory protective device.	
1	tive equipment. Keep unprotected persons away.	
1	ital precautions:	
Dilute with p	plenty of water.	
Do not allov	v to enter sewers/ surface or ground water.	
	d material for containment and cleaning up:	
	liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutrali		
	taminated material as waste according to section 13.	
	uate ventilation.	
• Protective A	ction Criteria for Chemicals	
• <i>PAC-1:</i>		
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	13 mg/m ³
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	• 90 mg/m ³
· PAC-2:		
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	140 mg/m³
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	990 mg/m³
	(Co	ntd. on page 4)
		- 05

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Trade name: BD54460 Part B (Hardener)

		(Contd. of page 3)
· PAC-3:		
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	850 mg/m ³
	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	5,900 mg/m ³
	o other sections	
See Section	7 for information on safe handling.	

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Trade name: BD54460 Part B (Hardener)

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical pro	operties
· General Information	
· Physical state	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	294.8 °C (562.6 °F)
· Flammability:	Not applicable.
• Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable.
· Auto igniting:	260 °C (500 °F)
• Decomposition temperature:	Not determined.
· pH-value:	Not determined.
· Viscosity:	
· Kinematic:	Not determined.
· Dynamic:	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
• Partition coefficient (n-octanol/water):	Not determined.
· Vapor pressure:	Not determined.
· Vapor pressure:	
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Particle characteristics	Not applicable.
• Other information	
· Appearance:	
· Form:	Fluid
Important information on protection of health	and
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
	(Contd. on page 6)

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Trade name: BD54460 Part B (Hardener)

(Contd. of page 5)

· Solvent conten	t:
· VOC content:	

· Solids content:

- · Change in condition
- \cdot Evaporation rate

0.00 % 0.0 g/l / 0.00 lb/gal 99.1 %

Not determined.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- *Conditions to avoid* No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

4246-51-9 3,3'-Oxybis(ethyleneoxy)bis(propylamine)

Oral LD50 4,310 mg/kg (rat)

Dermal LD50 2,510 mg/kg (rabbit)

Primary irritant effect:

• on the skin: Strong caustic effect on skin and mucous membranes.

· on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: Sensitization possible through skin contact.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

• Interactive effects No interactive effects between components are known.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

US

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Trade name: BD54460 Part B (Hardener)

• Alternative sources for toxicological information No non-standard sources for toxicological information where used.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects
- Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water
- Do not allow product to reach ground water, water course or sewage system, even in small quantities.
- Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

• Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information · UN-Number · DOT, IMDG, IATA UN1760 · UN proper shipping name $\cdot DOT$ Corrosive liquids, n.o.s. (3,3'-Oxybis(ethyleneoxy) *bis(propylamine))* CORROSIVE LIQUID, N.O.S. (3,3'-Oxybis(ethyleneoxy) · IMDG *bis(propylamine))* ·IATA Corrosive liquid, n.o.s. (3,3'-Oxybis(ethyleneoxy) *bis(propylamine))* • Transport hazard class(es) ·DOT · Class 8 Corrosive substances (Contd. on page 8) US

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Trade name: BD54460 Part B (Hardener)

	(Contd. of page 2
Label	8
IMDG, IATA	
\wedge	
8	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substances: reaction
	product: bisphenol-A-(epichlorhydrin) epoxy resin (numbe
	average molecular weight \leq 700)
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 30 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code)	: 80
EMS Number:	F-A,S-B
Segregation groups	(SGG18) Alkalis
Stowage Category	В
Stowage Code	SW2 Clear of living quarters.
UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (3,3'
-	OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)), 8, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 9)

⁻ US

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Trade name: BD54460 Part B (Hardener)

(Contd. of page 8)

· Hazardous Air Pollutants

None of the ingredients is listed. • **Proposition 65**

• Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value)

None of the ingredients is listed.

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: 3,3'-Oxybis(ethyleneoxy)bis(propylamine) reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) · Hazard statements Causes severe skin burns and eye damage. May cause an allergic skin reaction. · Precautionary statements Do not breathe dusts or mists. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves / eye protection / face protection. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 10)

Date of issue: 01/13/2025

Reviewed on 12/10/2024

Trade name: BD54460 Part B (Hardener)

(Contd. of page 9)

Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: -

Date of preparation 01/13/2025
Abbreviations and acronyms:
MDG: International Maritime Code for 1

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA:** Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin corrosion 1A: Skin corrosion/irritation - Category 1A Eye damage 1: Serious eye damage/eye irritation - Category 1 Sensitization - skin 1: Skin sensitisation - Category 1

US