



SDS Number: Page 1 of 7 Hard Surface Bonding Enhancer and Surface Cleaner

Revision No.: 3 Revision Date:3/17/2017

Section 1 IDENTIFICATION

Product Name: StonePrimer and Surface Cleaner for Hard Surfaces

Manufacturer: UltraTuf Adhesives 2954 N. Campbell Ave. #209 Tucson, Arizona, 85719 Phone: 1-520-333-2040 Fax: 520-294-5006 Email: <u>sales@ultratuf.biz</u> Website: www.ultratuf.biz

Trade Name: StonePrimer and Surface Cleaner

Materials Uses: StonePrimer and Surface Cleaner for Hard Surface Countertop Products

In Case of Emergency Contact CHEMTREC: 800-424-9300 (USA) 703-527-3887 (INTERNATIONAL)

Section 2 HAZARD IDENTIFICATION

GHS Classification:

CATEGORY	SIGNAL WORD	HAZARD STATEMENT(S)
Physical Flammable Liquids, Category	DANGER	H225 – Highly flammable liquid and vapor
Health Acute Oral Toxicity, Category 4 Skin Irritation, Category 3 Eye Irritation, Category 2A Skin Sensitization, Category 1	WARNING WARNING WARNING WARNING	H302 – Harmful if swallowed H316 – Causes mild skin irritation H319 – Causes serious eye irritation H317 – May cause an allergic skin reaction
Environmental Acute, Category 2 Chronic, Category 4		H401 – Toxic to aquatic life H413 – May cause long lasting harmful effects to aquatic life

GHS Precaution Statements:

Prevention:

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking.

SAFETY SDS DATA SHEET



SDS N	Number:
Page	2 of 7

Hard Surface Bonding Enhancer and Surface Cleaner

Revision No.: 3 Revision Date:3/17/2017

P261 – Avoid breathing dust/fume/mist/vapors/spray.

P264 – Wash hands (or other affected skin surfaces) thoroughly after handling.

P270 – Do not eat, drink, or smoke when using this product.

P273 – Avoid release to the environment

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P370/P378 – In case of fire: Use dry chemical or CO₂ to extinguish

P305/P351/P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301/P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

P302/P352 – IF ON SKIN: Wash with plenty of soap and water.

P333/P313 – If skin irritation or rash occurs get medical advice/attention.

Storage:

P403 - Store in a well-ventilated place.

P410 – Protect from sunlight.

P411 – Store at temperatures not exceeding 25°C (75°F).

Disposal:

P501 – Dispose of contents/containers in accordance with local/regional/national/international regulations.

Route of Entry: Eye contact, skin contact, inhalation, and ingestion.

Target Organs: Skin, eyes, respiratory tract, digestive tract, liver, kidney, olfactory and Central Nervous System (CNS).

Skin Contact: May cause irritation of the skin. Prolonged exposure may cause sensitization. Preexisting skin conditions may be aggravated by exposure to this material.

Eye Contact: May cause irritation and/or sensitization.

Respiratory Contact: Respiratory tract irritant. Prolonged exposure may result in dizziness, nausea, headache, and anesthetic effects. May cause sensitization. Preexisting respiratory conditions may be aggravated by exposure to this product. May cause CNS depression.

Ingestion: Not an expected route of entry. If ingested it may cause irritation to the gastrointestinal tract.

HMIS (United States)		NFPA (United States)	WHMIS (Canada): B2, D2B
Health	3		
Flammability	3	3	\frown
Reactivity	0		
PPE	В	3 0	





SDS Number: Page 3 of 7 Hard Surface Bonding Enhancer and Surface Cleaner

Revision No.: 3 Revision Date:3/17/2017

Section 3	COMPOSITION / INFORMATION ON INGREDIENTS		
	Name	CAS #	% by Weight
	Ethanol	64-17-5	80 – 95
	3-methacryloxypropyltrimethoxysilane	2530-85-0	5 – 10
	Methanol	67-56-1	.1 - 1

Section 4 FIRST-AID MEASURES

Skin: Remove contaminated clothing. Flush skin with water, then wash affected areas with soap and water. If irritation develops, seek medical attention. Wash or dispose of clothing before reuse.

- **Eye:** Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush if possible. Seek immediate medical attention.
- **Respiratory:** Remove patient to fresh air. If patient is having difficulty breathing, seek immediate medical attention. If not breathing, clear airway and start mouth-to-mouth artificial respiration (or use bag-mask respirator). Seek immediate medical attention.
- **Ingestion:** Give patient water to dilute material in stomach. DO NOT induce vomiting. Seek immediate medical attention. If vomiting occurs naturally, have person lean forward to reduce risk of aspiration. DO NOT give anything by mouth to an unconscious person.

Section 5 FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: In case of fire, use dry chemical or CO₂. Water spray may cause frothing.

Specific Hazards Arising from the Chemical: Sealed containers of enhancer may rupture violently at elevated temperatures due to extreme heat.

Special Protective Equipment and Precautions for Firefighters: Use self-contained breathing apparatus (SCBA) and protective clothing.

Flash Point and Method: 55°F (13°C). Fine mists may be explosive below the flash point. Tag Closed Cup. **Flammability Classification:** Class 1B.

Risk of Explosion due to Mechanical Impact: Not Applicable.

Risk of Explosion due to Static Discharge: Not Applicable. Bond and ground all equipment when transferring from one vessel to another.

Hazardous Products of Combustion: Carbon Oxides (CO and CO₂), and various Hydrocarbons. **Autoignition Temp.:** 365°F (185°C).

LEL: 3.6%.

UEL: 21.8%.

Section 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: For large spill or leak wear self-contained breathing apparatus (SCBA) and appropriate PPE.

Environmental Precautions: Keep out of sewers and drains.





SDS Number: Page 4 of 7 Hard Surface Bonding Enhancer and Surface Cleaner

Revision No.: 3 Revision Date:3/17/2017

Clean-Up Methods and Materials: Absorb with an inert material and place in an appropriate container for disposal.

Section 7 HANDLING AND STORAGE

Handling Precautions: Avoid breathing vapors. Use in a well-ventilated area. Wear rubber gloves (nitrile or butyl) and chemical resistant apron. Wear chemical splash goggles. Do not reuse empty containers.

Storage Precautions: Store in a cool, dry, well-ventilated area at temperatures less than 75°F (25°C). Storage above 212°F (100°C) may cause explosive decomposition. Avoid storage in direct sunlight. Keep containers closed when not in use. Keep away from heat sources, ignition sources, sparks, and open flames.

Section 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters and Exposures:

Material Name:

Ethanol (CAS 64-17-5):

3-methacryloxypropyltrimethoxysilane (CAS 2530-85-0) Methanol (CAS 67-56-1):

Exposure Limits:

OSHA PEL:	TWA 1,000 ppm
ACGIH TLV:	TWA 1,000 ppm
ACGIH TLV:	No data available
OSHA PEL:	TWA 200 ppm
ACGIH TLV:	TWA 200 ppm
	STEL 250 ppm

Engineering Controls: Provide adequate explosion proof ventilation (general or local exhaust). Ensure that a working eyewash and safety shower are in the work area.

Individual Protection Measures and PPE:

Eye / Face Protection: Wear safety glasses with side shields or splash goggles.

Skin Protection: Chemical resistant gloves (nitrile or butyl) and chemical resistant apron are recommended. **Respiratory Protection** In case of insufficient ventilation, wear an approved (NIOSH) respirator with organic vapor cartridge and dust/mist pre-filter.

Thermal Hazards: None.

Section 9 PHYSICAL AND CHEMICAL PROPERTIES

	Adhesive
Appearance:	Clear, colorless liquid
Odor:	Alcohol Odor
Odor Threshold:	Not Available
pH:	4.0 - 6.0
Melting Point / Freezing Point:	-78°F (-61°C)
Initial Boiling Point and Boiling Range:	173°F (78°C)
Flash Point and Method:	50°F (10°C) Tag Closed Cup
Evaporation Rate:	2.32 (butyl acetate = 1)
Flammability:	Class 1B
Lower Explosion Limit:	3.6%

SAFETY DATA SHEET



SDS Number: Page 5 of 7	Hard Surface Bonding Enhancer and Surface Cleaner	Revision No.: 3 Revision Date:3/17/2017
Upper Explosion Limit:	21.8%	
Vapor Pressure:	51.7 mm Hg @ 68°F (20°C)	
Vapor Density:	1.53 (air=1)	
Relative Density:	7.0 lbs./gallon	
Solubility(ies):	Not Available	
Partition Coefficient (n-Octanol in Water):	Not Applicable	
Auto-Ignition Temperature:	165ºF (185ºC)	
Decomposition Temperature:	Not Available	
Viscosity:	100 cP	
Percent Volatile:	90%	
Specific Gravity:	0.81	
VOC:	6.3 lbs./gallon	

Section 10 STABILITY AND REACTIVITY

Reactivity: Product is stable as supplied and when used as intended.

Chemical Stability: Not Available.

Possibility of Hazardous Reactions: None.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Avoid extreme temperatures, open flames, ignition sources, sparks, and direct sunlight. Materials to Avoid (Incompatibility): Oxidizing agents and conditions, and strong acids,

Hazardous Decomposition Products: Carbon Oxides (CO, CO₂) and various Hydrocarbons.

Section 11 TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals:	
Ethanol (CAS 64-17-5):	LC50 = 7093 ppm (4 hour inhalation, rat)
	LD50 = 7940 mg/kg (oral, rat)
	LD50 > 7550 mg/kg (dermal, rabbit)
3-methacryloxypropyltrimethoxysilane (CAS 2530-85-0)	LD50 > 2000 mg/kg (oral, rat)
	LD50 > 2000 mg/kg (dermal, rat)
Methanol (CAS 67-56-1)	LD50 = 5600 mg/kg (oral, rat)
	LD50 = 14200 mg/kg (oral, rabbit)
	LD50 = 15800 mg/kg (dermal, rabbit)
	LC50 = 81000 mg/m3 (rabbit)
	LC50 = 64000 ppm (4 hour inhalation, rat)

Acute Toxicity to Humans: This product has not been tested for human effects. No additional information. Chronic Toxicity to Animals: This product has not been tested for animal effects. No additional information. Chronic Toxicity to Humans: This product has not been tested for human effects. No additional information. Skin Corrosion / Irritation: Not Available.

Eye Damage / Irritation: Not Available.

Respiratory Sensitization: Not Available.





	Hard Surface	
SDS Number:	Bonding Enhancer	Revision No.: 3
Page 6 of 7	and Surface	Revision Date:3/17/2017
-	Cleaner	

Skin Sensitization: Not Available.
Mutagenicity: Classifiable as "none" for human.
Carcinogenicity: Not classifiable for human or animal.
Reproductive Toxicity: Not Available.
Teratogenic Effects: Classifiable as "none" for human.
STOST- Single Exposure: Not Available.
STOST – Repeated Exposure: Not Available.
Aspiration Hazard: Not Available.

Section 12 ECOLOGICAL INFORMATION

Ecotoxicity: This product contains components that may be harmful to aquatic organisms and may cause long term adverse effects in an aquatic environment.

Persistence and Degradability: Not Available.

Bioaccumulative Potential: This product contains components with the potential to bio-accumulate.

Mobility in Soil: Not Available.

Other Adverse Effects: Not Available.

Section 13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Liquid is considered Hazardous Waste Product per RCRA 40 CFR 261 and is classed as RCRA waste #D001. Spilled, contaminated, or waste material should be put into a suitable container and handled according to Federal, State, and local regulations. Contact a qualified waste management company for assistance. DANGER! Rags, steel wool, and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. Waste should be immediately placed in a sealed water filled container.

Section 14 TRANSPORT INFORMATION

UN Number: UN1170. UN Proper Shipping Name: Ethanol Solution (ethyl alcohol solution) Transport Hazard Class: 3 Packing Group: II. DOT Classification: UN1170, Hazard Class 3, Packing Group II, Limited Quantity. ADR / RID Classification: Class 3 ICAO/IATA Classification: Class 3 IMO/IMDG Classification: Class 3 Marine Pollutant: No additional information.

Section 15 REGULATORY INFORMATION

U.S. Federal Regulations

Chamical (8 CAS Number)	SARA 302	SARA 304	SARA 313	CERCLA	CAA	RCRA
Chemical (& CAS Number)	(EHS)TPQ	(EHS)Rq	de minimis	Rq	112(r) TQ	Code





_	DS Number: Page 7 of 7	Hard Surface Bonding Enhancer and Surface Cleaner	Bonding Enhancer Revision N and Surface Revision Date:3/17/2				
	Ethanol (CAS 64-17-5)		1.0				
	3-methacryloxypropyltrimethoxysilane (CAS 2530-85-0)		1.0	1000		U162	
	Methanol (CAS 67-56-1)		1.0	4400			
	All quantities in pounds.	· · · · · ·					

All quantities in pounds.

State Regulations

Chemical (& CAS Number)	CA Prop 65	MA RTK	MN RTK	NJ RTK	PA RTK	RI RTK
Ethanol (CAS 64-17-5)		Х	Х	Х	Х	Х
3-methacryloxypropyltrimethoxysilane (CAS 2530- 85-0)		Х	Х	Х	Х	Х
Methanol (CAS 67-56-1)	Х	Х	Х	Х	Х	Х

WARNING: This product contains a chemical know to the State of California to cause birth defects or other reproductive harm. Methanol (CAS 67-56-1) Revision Date: 2012-03-16

International Regulations

DSL (Canada): Components of this product are listed. Ethanol (CAS 64-17-5); 3methacryloxypropyltrimethoxysilane (CAS 2530-85-0); Methanol (CAS 67-56-1) EINECS: Not Available. WHMIS: B2, C, D2B.

Section 16 **OTHER INFORMATION**

Changes to This Revision: Revised 3/17/2017

Prepared By: Bruce Hart Telephone: USA - 520-440-1200 Internet: bruce@ultratuf.biz

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF SDS DOCUMENT