

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Identification	
Product identifier	
Trade name: <u>BD1020 Part A (Resi</u>	<u>n)</u>
Details of the supplier of the safety Manufacturer/Supplier: Big Dog Adhesives LLC 435 Harrison Street Elkhart IN 46516 USA	data sheet
Information department: Product s Emergency telephone number: During normal opening times: +1 (5 24 Hours: CHEMTREC 1-800-424-5	574) 350-2237
Hazard(s) identification	
Classification of the substance or m	nixture
GHS02 Flame	
Flammable liquids 2	H225 Highly flammable liquid and vapor.
GHS05 Corrosion	
Eye damage 1	H318 Causes serious eye damage.
GHS07	
Skin irritation 2	H315 Causes skin irritation.
Sensitization - skin 1	H317 May cause an allergic skin reaction.
Specific target organ toxicity (single	e exposure) 3 H335 May cause respiratory irritation.
Label elements GHS label elements The product is Hazard pictograms	classified and labeled according to the Globally Harmonized System (GHS)
GHS02 GHS05 GHS07	
Signal word Danger	
Hazard-determining components of	f labeling:
methyl methacrylate	(Contd. on pag

Page 1/11

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

	(Contd. of page 1)
Methacrylic Acid	
dodecyl methacrylate	
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye damage.	
May cause an allergic skin reaction.	
May cause respiratory irritation.	
· Precautionary statements	
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking	g.
Ground / bond container and receiving equipment.	
Use explosion-proof [electrical/ventilating/lighting] equipment.	
Use non-sparking tools.	
Take action to prevent static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or	shower].
If inhaled: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pres	ent and easy to do.
Continue rinsing.	
Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	<i>,</i> •
Dispose of contents/container in accordance with local/regional/national/international regular	nons.
· Information pertaining to particular dangers for man and environment:	
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 3	
Fire = 3	
3 0 Reactivity = 0	
• •	
HMIS-ratings (scale 0 - 4)	
HEALTH *3 $Health = *3$	
FIRE 3 $Fire = 3$	
REACTIVITY Reactivity = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• PBT: Not applicable.	
· vPvB: Not applicable.	
Classification according to (d)(1)(ii) of § 1910.1200	
The SDS issuer does not object to the classifications provided by importers or manufact	turers of precursor
products.	
	(Contd. on page 3)

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

· Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
80-62-6	methyl methacrylate	30–60%
142-90-5	dodecyl methacrylate	5-15%
79-41-4	Methacrylic Acid	1-5%
99-97-8	N,N-dimethyl-p-toluidine	0.1-1%

4 First-aid measures

• Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- *After swallowing: If symptoms persist consult doctor.*

• Most important symptoms and effects, both acute and delayed No further relevant information available. • Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)

⁻ US

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

		(Contd. of page 3)
· Protective	e Action Criteria for Chemicals	
· PAC-1:		
80-62-6	methyl methacrylate	17 ppm
142-90-5	dodecyl methacrylate	6.9 ppm
79-41-4	Methacrylic Acid	6.7 ppm
· PAC-2:		
80-62-6	methyl methacrylate	120 ppm
142-90-5	dodecyl methacrylate	76 ppm
79-41-4	Methacrylic Acid	61 ppm
· PAC-3:		
80-62-6	methyl methacrylate	570 ppm
142-90-5	dodecyl methacrylate	460 ppm
79-41-4	Methacrylic Acid	220 ppm
· Reference	e to other sections	I

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- *Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

- · Components with limit values that require monitoring at the workplace:
- The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

	2-6 methyl methacrylate
PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Long-term value: 410 mg/m³, 100 ppm
TLV	Short-term value: 410 mg/m³, 100 ppm
	Long-term value: 205 mg/m ³ , 50 ppm
	DSEN, A4

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

79-41-4 Methacrylic Acid

REL Long-term value: 70 mg/m³, 20 ppm Skin

TLV Long-term value: 70 mg/m³, 20 ppm

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- Avoid contact with the skin.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- General Information
- · Physical state
- · Color:
- · Odor:
- Odor threshold:
- Melting point/Melting range:
- Boiling point/Boiling range:
- · Flammability:

Liquid According to product specification Characteristic Not determined. Undetermined. 101°C (213.8°F) Highly flammable.

(Contd. on page 6)

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

	(Contd. of page
Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
Flash point:	10°C (50°F)
Auto igniting:	430°C (806°F)
Decomposition temperature:	Not determined.
pH-value:	Not determined.
Viscosity:	
Kinematic:	Not determined.
Dynamic:	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Vapor pressure at 20°C (68°F):	47 hPa (35.3 mm Hg)
Vapor pressure:	
Density at 20°C (68°F):	0.93104 g/cm ³ (7.76953 lbs/gal)
Relative density	Not determined.
Bulk density:	931 kg/m ³
Vapor density	Not determined.
Particle characteristics	Not applicable.
Other information	
Appearance:	
Form:	Viscous
Important information on protection of healt environment, and on safety.	th and
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosiv
	air/vapor mixtures are possible.
Solvent content:	
VOC content:	50 g/L mixed
Change in condition	0
Evaporation rate	Not determined.

10 Stability and reactivity

· *Reactivity* No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 29,730 mg/kg (rat)

(Contd. on page 7)

US

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

	LD50		
		l methacrylate	
Oral		7,872 mg/kg (rat)	
79-41-4		crylic Acid	
Oral	LD50	1,332 mg/kg (mouse)	
		1,320 mg/kg (rat)	
Dermal	LD50	500 mg/kg (rabbit)	
Additio	nal toxi	Sensitization possible through skin contact. icological information:	
• Addition The pro Irritant • Interact • Carcino	nal toxi oduct sho tive effe ogenic c	icological information: ows the following dangers according to internally approved calculation methods for p ects No interactive effects between components are known. categories	preparation.
• Addition The pro Irritant • Interact • Carcino • IARC (1	nal toxi oduct sho tive effe ogenic c Interna	icological information: ows the following dangers according to internally approved calculation methods for p ects No interactive effects between components are known. categories tional Agency for Research on Cancer)	
Addition The pro Irritant Interact Carcino IARC (1 80-62-6	nal toxi oduct sh tive effe ogenic c Interna o methy	icological information: ows the following dangers according to internally approved calculation methods for p ects No interactive effects between components are known. categories tional Agency for Research on Cancer) I methacrylate	3
• Addition The pro Irritant • Interact • Carcina • Carcina 80-62-6 99-97-8	nal toxi oduct sho tive effe ogenic c Interna 5 methy 3 N,N-d	icological information: ows the following dangers according to internally approved calculation methods for p ects No interactive effects between components are known. categories tional Agency for Research on Cancer) I methacrylate limethyl-p-toluidine	
 Addition The pro Irritant Interact Carcina IARC (18) 80-62-6 99-97-8 NTP (N 	nal toxi oduct sho tive effe ogenic c Interna [5] methy [3] N,N-d National	icological information: ows the following dangers according to internally approved calculation methods for p ects No interactive effects between components are known. categories tional Agency for Research on Cancer) I methacrylate limethyl-p-toluidine Toxicology Program)	3
 Addition The pro Irritant Interact Carcina IARC (18) 80-62-6 99-97-8 NTP (N 	nal toxi oduct sho tive effe ogenic c Interna [5] methy [3] N,N-d National	icological information: ows the following dangers according to internally approved calculation methods for p ects No interactive effects between components are known. categories tional Agency for Research on Cancer) I methacrylate limethyl-p-toluidine	3
Addition The pro Irritant Theract Carcina 1ARC (1 80-62-6 99-97-8 NTP (N None of	nal toxi oduct sho tive effe ogenic c Interna [] methy [] N,N-d National f the ing	icological information: ows the following dangers according to internally approved calculation methods for p ects No interactive effects between components are known. categories tional Agency for Research on Cancer) I methacrylate limethyl-p-toluidine Toxicology Program)	3
Addition The pro Irritant Carcina Carcina 1ARC (1 80-62-6 99-97-8 NOTP (N None of OSHA-	nal toxi duct sh tive effe ogenic c Interna [methy] N,N-d National f the ing Ca (Occ	icological information: ows the following dangers according to internally approved calculation methods for p ects No interactive effects between components are known. categories tional Agency for Research on Cancer) I methacrylate limethyl-p-toluidine Toxicology Program) redients is listed.	3

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- *Persistence and degradability* No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects
- Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

(Contd. on page 8)

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN1133
UN proper shipping name	
DOT, IATA	Adhesives
IMDG	ADHESIVES
Transport hazard class(es)	
DOT	
RAMABLE LOUD	
3	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Special precautions for user	Warning: Flammable liquids

(Contil of mago 8)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

		(Contd. of page 8)
· Hazard identification number (Kem)	er code): 30	
EMS Number:	F-E,S-D	
· Stowage Category	В	
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III	

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

80-62-6 methyl methacrylate

· Proposition 65

· Chemicals known to cause cancer:

99-97-8 N,N-dimethyl-p-toluidine

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

80-62-6 methyl methacrylate

E, NL

A4

• *TLV* (*Threshold Limit Value*) 80-62-6 methyl methacrylate

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• Hazard-determining components of labeling: methyl methacrylate

(Contd. on page 10)

US -

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

	(Contd. of page 9)
Methacrylic Acid	
dodecyl methacrylate	
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye damage.	
May cause an allergic skin reaction.	
May cause respiratory irritation.	
· Precautionary statements	
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
Ground / bond container and receiving equipment.	
Use explosion-proof [electrical/ventilating/lighting] equipment.	
Use non-sparking tools.	
Take action to prevent static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or show	ver].
If inhaled: Remove person to fresh air and keep comfortable for breathing.	-
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present	and easy to do.
Continue rinsing.	2
Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations	<i>š</i> .
• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: -

- Date of preparation 04/02/2025
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

(Contd. on page 11)

Date of issue: 04/02/2025

Reviewed on 04/02/2025

Trade name: BD1020 Part A (Resin)

(Contd. of page 10)

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable liquids 2: Flammable liquids – Category 2 Skin irritation 2: Skin corrosion/irritation – Category 2 Eye damage 1: Serious eye damage/eye irritation – Category 1 Sensitization - skin 1: Skin sensitisation – Category 1 Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3