

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Page 1/10

Identification	
Product identifier	
Trade name: <u>BD560 Part B (Activate</u>	<u>or)</u>
Details of the supplier of the safety d Manufacturer/Supplier: Big Dog Adhesives LLC 435 Harrison Street ELKHART, IN 46516	ata sheet
USA	
Information department: Product say Emergency telephone number: During normal opening times: +1 (52 24 Hours: CHEMTREC 1-800-424-93	20) 271-7313
Hazard(s) identification	
Classification of the substance or mi	xture
GHS02 Flame	
Flammable liquids 2	H225 Highly flammable liquid and vapor.
GHS07	
Skin irritation 2	H315 Causes skin irritation.
Sensitization - skin 1	H317 May cause an allergic skin reaction.
Specific target organ toxicity (single e	exposure) 3 H335 May cause respiratory irritation.
Label elements GHS label elements The product is cl Hazard pictograms GHS02 GHS07	lassified and labeled according to the Globally Harmonized System (GHS).
Signal word Danger	
Hazard-determining components of a methyl methacrylate Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction.	labeling:
May cause respiratory irritation.	
	(Contd. on page

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Trade name: BD560 Part B (Activator)

	ontd. of page 1)
· Precautionary statements	
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
Ground / bond container and receiving equipment.	
Use explosion-proof [electrical/ventilating/lighting] equipment.	
Use non-sparking tools.	
Take action to prevent static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]	
If inhaled: Remove person to fresh air and keep comfortable for breathing.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
· Information pertaining to particular dangers for man and environment:	
· Classification system:	
· NFPÅ ratings (scale 0 - 4)	
Health = 1 Fire = 3 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
HEALTH1Health = 1FIRE3Fire = 3REACTIVITY0Reactivity = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• PBT: Not applicable.	
• vPvB: Not applicable.	
· Classification according to (d)(1)(ii) of § 1910.12000	
The SDS issuer does not object to the classifications provided by importers or manufacturers of	of precursor
products.	
· Hazards not otherwise classified	
There are no adverse physical or health effects known that are not covered by the hazard classes of	the Hazard
Communications Standard.	
3 Composition/information on ingredients	
Chomical characterization, Mixtures	
• Chemical characterization: Mixtures	
• Description: Mixture of the substances listed below with nonhazardous additions.	
Dangerous components:	
	1

80-62-6 methyl methacrylate

45–70% * (Contd. on page 3)

US

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Trade name: BD560 Part B (Activator)

(Contd. of page 2)

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

· Protective Action Criteria for Chemicals

· PAC-1:

All components have the value 17 ppm.

· PAC-2:

All components have the value 120 ppm.

· PAC-3:

All components have the value 570 ppm.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Trade name: BD560 Part B (Activator)

(Contd. of page 3)

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- *Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.*
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm

REL Long-term value: 410 mg/m³, 100 ppm

TLV Short-term value: 100 ppm Long-term value: 50 ppm DSEN, A4

• *Additional information:* The lists that were valid during the creation were used as basis.

• Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Trade name: BD560 Part B (Activator)

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

 Information on basic physical and chemical prop General Information Physical state Color: Odor: Odor threshold: Melting point/Melting range: Boiling point/Boiling range: Flammability: Explosion limits: Lower: Upper: Flash point: 	Fluid According to product specification Characteristic Not determined. Undetermined. 101 °C (213.8 °F) Highly flammable. 2.1 Vol % 12.5 Vol %
 Physical state Color: Odor: Odor threshold: Melting point/Melting range: Boiling point/Boiling range: Flammability: Explosion limits: Lower: Upper: 	According to product specification Characteristic Not determined. Undetermined. 101 °C (213.8 °F) Highly flammable. 2.1 Vol % 12.5 Vol %
Color: Odor: Odor threshold: Melting point/Melting range: Boiling point/Boiling range: Flammability: Explosion limits: Lower: Upper:	According to product specification Characteristic Not determined. Undetermined. 101 °C (213.8 °F) Highly flammable. 2.1 Vol % 12.5 Vol %
Odor: Odor threshold: Melting point/Melting range: Boiling point/Boiling range: Flammability: Explosion limits: Lower: Upper:	Characteristic Not determined. Undetermined. 101 °C (213.8 °F) Highly flammable. 2.1 Vol % 12.5 Vol %
Odor threshold: Melting point/Melting range: Boiling point/Boiling range: Flammability: Explosion limits: Lower: Upper:	Not determined. Undetermined. 101 °C (213.8 °F) Highly flammable. 2.1 Vol % 12.5 Vol %
Melting point/Melting range: Boiling point/Boiling range: Flammability: Explosion limits: Lower: Upper:	Undetermined. 101 °C (213.8 °F) Highly flammable. 2.1 Vol % 12.5 Vol %
Boiling point/Boiling range: Flammability: Explosion limits: Lower: Upper:	101 °C (213.8 °F) Highly flammable. 2.1 Vol % 12.5 Vol %
Flammability: Explosion limits: Lower: Upper:	Highly flammable. 2.1 Vol % 12.5 Vol %
Explosion limits: Lower: Upper:	2.1 Vol % 12.5 Vol %
Lower: Upper:	12.5 Vol %
Upper:	12.5 Vol %
. Flach noint.	
	10 °C (50 °F)
Auto igniting:	430 °C (806 °F)
Decomposition temperature:	Not determined.
pH-value:	Not determined.
Viscosity:	
Kinematic:	Not determined.
Dynamic:	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
· Vapor pressure at 20 °C (68 °F):	47 hPa (35.3 mm Hg)
Vapor pressure:	
Density at 20 °C (68 °F):	0.94 g/cm ³ (7.8443 lbs/gal)
Relative density	Not determined.
Bulk density:	940 kg/m ³
· Vapor density	Not determined.
Particle characteristics	Not applicable.
Other information	
Appearance:	
Form:	Viscous
Important information on protection of health an	d
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
	(Contd. on page 6)

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Trade name: BD560 Part B (Activator)

	(Contd. of page 5)
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Solvent content: VOC content:	< 50 g/L (mixed)
• Change in condition • Evaporation rate	Not determined.

10 Stability and reactivity

· *Reactivity* No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

• *Conditions to avoid* No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

80-62-6 methyl methacrylate

Oral LD50 7,872 mg/kg (rat)

Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: No irritating effect.

• Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Interactive effects No interactive effects between components are known.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

All components have the value 3.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

• Persistence and degradability No further relevant information available.

(Contd. on page 7)

US

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Trade name: BD560 Part B (Activator)

(Contd. of page 6)

- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- \cdot *Mobility in soil* No *further relevant information available.*
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects
- Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water
- Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, IMDG, IATA	UN1133	
UN proper shipping name		
DOT, IATA	Adhesives	
IMDG	ADHESIVES	
Transport hazard class(es)		
DOT		
FLAMMABLE LIQUID		
3		
Class	3 Flammable liquids	
Label	3	
	5	
IMDG, IATA		
V		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, IMDG, IATA	III	
Environmental hazards:	Not applicable.	

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Trade name: BD560 Part B (Activator)

	(Contd. of page
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
~ '	On cargo aircraft only: 220 L
·IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code)	: 33
EMS Number:	F-E,S-D
Stowage Category	В
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings): All ingredients are listed.

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

All components have the value E, NL.

(Contd. on page 9)

[—] US

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Trade name: BD560 Part B (Activator)

(Contd. of page 8)

• *TLV (Threshold Limit Value) All components have the value A4.*

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger · Hazard-determining components of labeling: methyl methacrylate · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground / bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take action to prevent static discharge. Avoid breathing dust/fume/gas/mist/vapors/sprav Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: -

• Date of preparation 01/22/2025

(Contd. on page 10)

US

Date of issue: 01/22/2025

Reviewed on 01/22/2025

Trade name: BD560 Part B (Activator)

	(Contd. of page
Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flammable liquids 2: Flammable liquids – Category 2	
Skin irritation 2: Skin corrosion/irritation – Category 2	
Sensitization - skin 1: Skin sensitisation – Category 1	
Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3	