

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

1 Identification

- **Product identifier**
- **Trade name:** SeamKing Pro SK1800 Chameleon Part A (Resin)
- **Details of the supplier of the safety data sheet**
 Big Dog Adhesives LLC
 435 Harrison Street
 Elkhart IN 46516
 USA
- **Information department:** Product safety department
- **Emergency telephone number:**
 During normal opening times: +1 (574) 350-2237
 24 Hours: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1B

H350 May cause cancer.

Reproductive toxicity 2

H361 Suspected of damaging fertility or the unborn child.



GHS07

Skin irritation 2

H315 Causes skin irritation.

Sensitization - skin 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity (single exposure) 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: SeamKing Pro SK1800 Chameleon Part A (Resin)

(Contd. of page 1)

· Hazard-determining components of labeling:

methyl methacrylate

Styrene

N,N-dimethyl-p-toluidine

ethyl acrylate

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground / bond container and receiving equipment.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Use non-sparking tools.

Take action to prevent static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Information pertaining to particular dangers for man and environment:
· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 1

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)


Health = *1

Fire = 3

Reactivity = 0

· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: SeamKing Pro SK1800 Chameleon Part A (Resin)

(Contd. of page 2)

· **Classification according to (d)(1)(ii) of § 1910.1200**

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

· **Hazards not otherwise classified**

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

80-62-6	methyl methacrylate	≥20–≤30%
100-42-5	Styrene	0.1–1%
99-97-8	N,N-dimethyl-p-toluidine	0.1–1%
140-88-5	ethyl acrylate	≥0.1–<1%

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: SeamKing Pro SK1800 Chameleon Part A (Resin)

(Contd. of page 3)

Ensure adequate ventilation.

· Protective Action Criteria for Chemicals

· PAC-1:		
80-62-6	methyl methacrylate	17 ppm
100-42-5	Styrene	20 ppm
140-88-5	ethyl acrylate	8.3 ppm
· PAC-2:		
80-62-6	methyl methacrylate	120 ppm
100-42-5	Styrene	130 ppm
140-88-5	ethyl acrylate	36 ppm
· PAC-3:		
80-62-6	methyl methacrylate	570 ppm
100-42-5	Styrene	1100* ppm
140-88-5	ethyl acrylate	240 ppm

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.· **Information about storage in one common storage facility:** Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate	
PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Long-term value: 410 mg/m ³ , 100 ppm
TLV	Short-term value: 410 mg/m ³ , 100 ppm
	Long-term value: 205 mg/m ³ , 50 ppm
	DSEN, A4

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: **SeamKing Pro SK1800 Chameleon Part A (Resin)**

(Contd. of page 4)

100-42-5 Styrene

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m ³ , 100 ppm Long-term value: 215 mg/m ³ , 50 ppm
TLV	Short-term value: 20 ppm Long-term value: 10 ppm BEL, OTO, A3

99-97-8 N,N-dimethyl-p-toluidine

WEEL	Long-term value: 0.5 ppm
------	--------------------------

140-88-5 ethyl acrylate

PEL	Long-term value: 100 mg/m ³ , 25 ppm Skin
REL	See Pocket Guide App. A
TLV	Short-term value: 61 mg/m ³ , 15 ppm Long-term value: 21 mg/m ³ , 5 ppm A4

Ingredients with biological limit values:**100-42-5 Styrene**

BEI	400 mg/g creatinine Medium: urine Time: end of shift Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)
	40 µg/L Medium: urine Time: end of shift Parameter: Styrene

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: SeamKing Pro SK1800 Chameleon Part A (Resin)

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Liquid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

101°C (213.8°F)

· **Flammability:**

Highly flammable.

· **Explosion limits:**

· **Lower:**

2.1 Vol %

· **Upper:**

12.5 Vol %

· **Flash point:**

10°C (50°F)

· **Auto igniting:**

430°C (806°F)

· **Decomposition temperature:**

Not determined.

· **pH-value:**

Not determined.

· **Viscosity:**

· **Kinematic:**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility in / Miscibility with**

· **Water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):**

Not determined.

· **Vapor pressure at 20°C (68°F):**

47 hPa (35.3 mm Hg)

· **Vapor pressure:**

· **Density at 20°C (68°F):**

0.9399 g/cm³ (7.84347 lbs/gal)

· **Relative density**

Not determined.

· **Bulk density:**

940 kg/m³

· **Vapor density**

Not determined.

· **Particle characteristics**

Not applicable.

· **Other information**

· **Appearance:**

· **Form:**

Fluid

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: SeamKing Pro SK1800 Chameleon Part A (Resin)

(Contd. of page 6)

· **Important information on protection of health and environment, and on safety.**

· **Ignition temperature:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Solvent content:**

· **VOC content:**

< 50 g/L mixed

· **Change in condition**

· **Evaporation rate**

Not determined.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** No further relevant information available.

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	22,748 mg/kg
Dermal	LD50	68,244 mg/kg
Inhalative	LC50/4 h	682 mg/l

80-62-6 methyl methacrylate

Oral	LD50	7,872 mg/kg (rat)
------	------	-------------------

100-42-5 Styrene

Oral	LD50	5,000 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)

140-88-5 ethyl acrylate

Oral	LD50	800 mg/kg (rat)
Dermal	LD50	1,834 mg/kg (rabbit)
Inhalative	LC50/4 h	2,180 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** No irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Interactive effects** No interactive effects between components are known.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: SeamKing Pro SK1800 Chameleon Part A (Resin)

(Contd. of page 7)

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

80-62-6	methyl methacrylate	3
100-42-5	Styrene	2A
99-97-8	N,N-dimethyl-p-toluidine	2B
140-88-5	ethyl acrylate	2B

· **NTP (National Toxicology Program)**

100-42-5	Styrene	R
----------	---------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Alternative sources for toxicological information**

No non-standard sources for toxicological information where used.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects**· **Additional ecological information:**· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

· **Waste treatment methods**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**· **DOT, IMDG, IATA** UN1133· **UN proper shipping name**

· **DOT, IATA** Adhesives

· **IMDG** ADHESIVES

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: SeamKing Pro SK1800 Chameleon Part A (Resin)

(Contd. of page 8)

· **Transport hazard class(es)**· **DOT**· **Class**

3 Flammable liquids

· **Label**

3

· **IMDG, IATA**· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**· **DOT, IMDG, IATA**

III

· **Environmental hazards:**

Not applicable.

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **DOT**· **Quantity limitations**

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· **IMDG**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):**

30

· **EMS Number:**

F-E,S-D

· **Stowage Category**

B

· **UN "Model Regulation":**

UN 1133 ADHESIVES, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

80-62-6 methyl methacrylate

100-42-5 Styrene

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: SeamKing Pro SK1800 Chameleon Part A (Resin)

(Contd. of page 9)

140-88-5 ethyl acrylate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

80-62-6 methyl methacrylate

100-42-5 Styrene

140-88-5 ethyl acrylate

· Proposition 65
· Chemicals known to cause cancer:

100-42-5 Styrene

99-97-8 N,N-dimethyl-p-toluidine

140-88-5 ethyl acrylate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

80-62-6 methyl methacrylate

E, NL

· TLV (Threshold Limit Value)

80-62-6 methyl methacrylate

A4

100-42-5 Styrene

A4

140-88-5 ethyl acrylate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

140-88-5 ethyl acrylate

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms


GHS02



GHS07



GHS08

· Signal word Danger

· Hazard-determining components of labeling:

methyl methacrylate

Styrene

N,N-dimethyl-p-toluidine

ethyl acrylate

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause cancer.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: **SeamKing Pro SK1800 Chameleon Part A (Resin)**

(Contd. of page 10)

*Suspected of damaging fertility or the unborn child.**May cause respiratory irritation.***· Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**Ground / bond container and receiving equipment.**Use explosion-proof [electrical/ventilating/lighting] equipment.**Use non-sparking tools.**Take action to prevent static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].**If inhaled: Remove person to fresh air and keep comfortable for breathing.**IF exposed or concerned: Get medical advice/attention.**Call a poison center/doctor if you feel unwell.**Specific treatment (see on this label).**Take off contaminated clothing and wash it before reuse.**If skin irritation or rash occurs: Get medical advice/attention.**In case of fire: Use CO₂, powder or water spray to extinguish.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· National regulations:****· Information about limitation of use:***Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.**Exceptions can be made by the authorities in certain cases.***· Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.***· Department issuing SDS:** *Environment protection department.***· Contact:** -**· Date of previous version** 06/09/2025**· Date of preparation** 06/09/2025**· Abbreviations and acronyms:***IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative*

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/09/2025

Reviewed on 06/09/2025

Trade name: SeamKing Pro SK1800 Chameleon Part A (Resin)

(Contd. of page 11)

*NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable liquids 2: Flammable liquids – Category 2**Skin irritation 2: Skin corrosion/irritation – Category 2**Sensitization - skin 1: Skin sensitisation – Category 1**Carcinogenicity 1B: Carcinogenicity – Category 1B**Reproductive toxicity 2: Reproductive toxicity – Category 2**Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3**. * Data compared to the previous version altered.*

US