



Date of issue: 02/03/2025 Reviewed on 02/03/2025

## 1 Identification

· Product identifier

· Trade name: ZipTac 2

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Big Dog Adhesives LLC 435 Harrison Street Elkhart, IN 46516 USA

· Information department: Product safety department

· Emergency telephone number:

*During normal opening times:* +1 (800) 252-4144

24 Hours: CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye irritation 2A H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

CHSUS

· Signal word Danger

(Contd. on page 2)

Date of issue: 02/03/2025 Reviewed on 02/03/2025

Trade name: ZipTac 2

(Contd. of page 1)

### · Hazard-determining components of labeling:

acetone

*N*,*N*-dimethyl-p-toluidine

#### · Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

Obtain special instructions before use.

*Do not handle until all safety precautions have been read and understood.* 

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

*Ground / bond container and receiving equipment.* 

*Use explosion-proof [electrical/ventilating/lighting] equipment.* 

Use non-sparking tools.

Take action to prevent static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

*Call a poison center/doctor if you feel unwell.* 

Get medical advice/attention if you feel unwell.

*If eye irritation persists: Get medical advice/attention.* 

*In case of fire: Use CO2, powder or water spray to extinguish.* 

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Information pertaining to particular dangers for man and environment:
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Classification according to (d)(1)(ii) of § 1910.12000

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

(Contd. on page 3)

Date of issue: 02/03/2025 Reviewed on 02/03/2025

Trade name: ZipTac 2

(Contd. of page 2)

Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

	· Dangeroi	Dangerous components:	
I	67-64-1 d	acetone	95-100% *
I	99-97-8	N,N-dimethyl-p-toluidine	< 5%

<sup>\*</sup> Actual concentration ranges are withheld as a trade secret.

## 4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Date of issue: 02/03/2025 Reviewed on 02/03/2025

Trade name: ZipTac 2

(Contd. of page 3)

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Protective Action Criteria for Chemicals

· <i>PAC-1</i> :	
67-64-1	200 ppm

· PAC-2:

67-64-1 acetone 3200\* ppm

· *PAC-3*:

67-64-1 acetone 5700\* ppm

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· Precautions for safe handling

 ${\it Ensure good ventilation/exhaustion \ at \ the \ workplace}.$ 

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

Control parameters

67-64-	-1 acetone	
PEL	Long-term value: 2400 mg/m³, 1000 ppm	
REL	Long-term value: 590 mg/m³, 250 ppm	
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI	

(Contd. on page 5)

Date of issue: 02/03/2025 Reviewed on 02/03/2025

Trade name: ZipTac 2

(Contd. of page 4)

### · Ingredients with biological limit values:

#### 67-64-1 acetone

BEI 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Fluid

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Physical state

· Color: Amber colored · Odor: Pungent

· *Odor threshold:* Not determined.

(Contd. on page 6)

Date of issue: 02/03/2025 Reviewed on 02/03/2025

Trade name: ZipTac 2

(Contd. of page 5)

• *Melting point/Melting range:* -94.7°C (-138.5°F)

• **Boiling point/Boiling range:** 55.8–56.6°C (132.4–133.9°F)

• Flammability: Highly flammable.

Explosion limits:

 · Lower:
 2.6 Vol %

 · Upper:
 13 Vol %

 · Flash point:
 -17°C (1.4°F)

 · Auto igniting:
 465°C (869°F)

 · Decomposition temperature:
 Not determined.

 · pH-value:
 Not determined.

· Viscosity:

• Kinematic: Not determined. • Dynamic at 20°C (68°F): 32 mPas

Solubility in / Miscibility with

• Water: Fully miscible.
• Partition coefficient (n-octanol/water): Not determined.

• Vapor pressure at 20°C (68°F): 233 hPa (174.8 mm Hg) • Vapor pressure at 50°C (122°F): 800 hPa (600 mm Hg)

• Density at 20°C (68°F): 0.74544-0.84505 g/cm³ (6.2207-7.05194 lbs/gal)

Relative density
 Vapor density
 Particle characteristics
 Not determined.
 Not applicable.

· Other information

· Appearance:

· Form: Liquid

Important information on protection of health and

environment, and on safety.

• Ignition temperature: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive

air/vapor mixtures are possible.

· Solvent content:

• **VOC content:** 0.0 g/l / 0.00 lb/gal

· Change in condition

• Evaporation rate Not determined.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

US

Reviewed on 02/03/2025 Date of issue: 02/03/2025

Trade name: ZipTac 2

(Contd. of page 6)

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
ATE (Acu	te Toxicity	Estimate)
Oral	LD50	2,500–10,000 mg/kg
Dermal	LD50	7,500–30,000 mg/kg
Inhalative	LC50/4 h	75–300 mg/l

67-64-1 acetone		
Oral		5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Interactive effects No interactive effects between components are known.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

99-97-8 N,N-dimethyl-p-toluidine

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Date of issue: 02/03/2025 Reviewed on 02/03/2025

Trade name: ZipTac 2

(Contd. of page 7)

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
DOT, IMDG, IATA	UN1090
UN proper shipping name	
DOT, IATA IMDG	Acetone ACETONE
	ACETONE
Transport hazard class(es)	
DOT	
FLAMMAGE LOUD	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	IL .
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Date of issue: 02/03/2025 Reviewed on 02/03/2025

Trade name: ZipTac 2

(Contd. of page 8)

· Special precautions for user Warning: Flammable liquids

· Hazard identification number (Kemler code): 33

• EMS Number: F-E,S-D

· Stowage Category E

· UN "Model Regulation": UN 1090 ACETONE, 3, II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

99-97-8 N,N-dimethyl-p-toluidine

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

67-64-1 acetone

· TLV (Threshold Limit Value)

67-64-1 acetone

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

· **Signal word** Danger

Date of issue: 02/03/2025 Reviewed on 02/03/2025

Trade name: ZipTac 2

(Contd. of page 9)

### · Hazard-determining components of labeling:

acetone

N,N-dimethyl-p-toluidine

· Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground / bond container and receiving equipment.

*Use explosion-proof [electrical/ventilating/lighting] equipment.* 

Use non-sparking tools.

Take action to prevent static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

*Call a poison center/doctor if you feel unwell.* 

Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

*In case of fire: Use CO2, powder or water spray to extinguish.* 

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: -
- · Date of preparation 02/03/2025
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 11)

(Contd. of page 10)

## Safety Data Sheet acc. to OSHA HCS

Date of issue: 02/03/2025 Reviewed on 02/03/2025

Trade name: ZipTac 2

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable liquids 2: Flammable liquids – Category 2

Eye irritation 2A: Serious eye damage/eye irritation – Category 2A Carcinogenicity 2: Carcinogenicity – Category 2

Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3 Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) - Category 2